CiteSeer Find: hardware/software co-simulation   **Documents**   **Citations**

Searching for **PHRASE hardware software co simulation**.
Restrict to: Header Title Order by: Citations Hubs Usage Date Try: Amazon B&N Google (RI) Google (Web) CSB
DBLP
37 documents found. **Order: citations weighted by year.**

An Efficient Implementation of Reactivity for Modeling.. - Liao, Tjiang, Gupta (1997) (Correct) (20 citations)
of the issues in co-design such as **hardware-software co-simulation** [9] 15]One of the most pressing
language would facilitate seamless **hardware-software co-simulation**. Moreover, a single language would
wwwbib.informatik.tu-muenchen.de/cdviews/dac97/papers/1997/dac97/htmfiles/sun_sgi/../../psfiles/03_4.ps

Dynamic Communication Models in Embedded System Co-Simulation - Hines, Borriello (1997) (Correct) (17 citations)
simulation speedups. 1 Introduction **Hardware-software co-simulation** is used to validate both the
give better feedback. 7 Conclusion **Hardware-software co-simulation** of embedded systems can perform
S. G. An engineering environment for **hardware/software co-simulation**. In 29th ACM/IEEE Design Automation
www.cs.washington.edu/research/projects/lis/www/papers/postscript/hines-dac97.ps

ISDL: An Instruction Set Description Language for.. - Hadjiyiannis, Hanono.. (1997) (Correct) (16 citations)
tools for code generation and **hardware-software co-simulation** have become essential parts of the
herkules.informatik.tu-chemnitz.de/proceedings/dac-97/papers/1997/dac97/htmfiles/sun_sgi/../../pdffiles/18_3.pdf

Software Performance Estimation Strategies in a.. - Bammi, Harcourt.. (2000) (Correct) (2 citations)
estimation, coupled with a fast **hardware/software co-simulation** framework, is a key enabler to
www.sigda.org/Archives/ProceedingArchives/Codes/Codes2000/papers/2000/codes00/htmfiles/SUN_SGI/../../pdffiles/04_5.pdf

POLIS - A design environment for control-dominated .. - Balarin, Chiodo.. (1999) (Correct) (2 citations)
: 48 6 **Hardware-software co-simulation** 51 6.1 Co-simulation and
than via mathematical analysis. **Hardware /software co-simulation** is generally performed with separate
is not implemented either. 50 6 **Hardware-software co-simulation** This section describes the various
ic.eecs.berkeley.edu/pub/HWSW/polis_man.0.4.ps.gz

Efficient Power Estimation Techniques for HW/SW Systems - Marcello Lajolo (1999) (Correct) (2 citations)
estimates. However, as in the case of **hardware/software co-simulation**, the communication and
emission of an event, etc.Prior to **hardware/software co-simulation**, the software parts of the system
65-70, Mar. 1998. 15] J. Rowson. **Hardware/software co-simulation**. In Proc. Design Automation Conf.
auri.ucsd.edu/dey/papers/voltas99.ps

Models and Methods for HW/SW Intellectual Property.. - Ortega, Lavagno, Borriello (1998) (Correct) (3 citations)
we discuss various strategies for **hardware/software co-simulation**, with special attention to the
validation issues, in terms of both **hardware-software co-simulation**, and of formal verification. 1.1
www-cad.eecs.berkeley.edu/Respep/Research/hsc/class/ee249/papers/asi98_submitted.ps.gz

Trends in Embedded Systems Technology: An Industrial Perspective - Pierre Paulin (1995) (Correct) (4 citations)
commercial processor core. 3. CoGen, a **hardware-software co-simulation** interface generator. DRAFT: NATO
cwc.ucsd.edu/courses/billlin/S97/ece260C/reading/nato95.ps.gz

The Design of Mixed Hardware/Software Systems - Adams, Thomas (1996) (Correct) (4 citations)
tasks hardware-software partitioning **hardware-software co-simulation** system design hardware-software
into every subset of this diagram. 3.1 **Hardware/software co-simulation** Simulation of hardware/software
systems, sometimes called **hardware -software co-simulation**, presents the problem of modeling
jerry.c-lab.de/~wolfgang/TUTORIALS/96/34_1.ps.Z

Hardware, Software and Mechanical Cosimulation for.. - Le Marrec Valderrama (1998) (Correct) (2 citations)
is quite recent. This started with **hardware software co-simulation** (4]5]9]3]and now it is
Hagen and H. Meyr. Timed and untimed **hardwaresoftware co-simulation**: Application and efficient
1993. 5] S. Lee and J. Rabaey. A **hardware-software cosimulation** environment. International Workshop
tima-cmp.imag.fr/Homepages/cosmos/documents/lemarrec.ps

Architecture Description Languages for Systems-on-Chip .. - Tomiyama, Halambi.. (1999)   (Correct)   (1 citation)
of hardware, debugging of software, **hardware/software co-simulation**, and so on. A variety of simulators
in the ADL specification)Then, **hardware/software co-simulation** is performed using the generated
www.cecs.uci.edu/~aces/Pubs/apchdl99.ps

Pia: A Framework for Embedded System Co-simulation with Dynamic .. - Hines (1996)   (Correct)   (2 citations)
simulation speedups. 1 Introduction **Hardware-software co-simulation** is used to verify the correctness of
give better feedback. 7 Conclusion **Hardware-software co-simulation** of embedded systems can perform
Tell. An engineering environment for **hardware /software co-simulation**. In 29th ACM/IEEE Design Automation
www.cs.washington.edu/research/lis/papers/postscript/hines-tr.ps

Compiled Simulation of Programmable DSP Architectures - Zivojnovic, Tjiang, Meyr (1995)   (Correct)   (1 citation)
a simulator of the hardware portions (**hardware/software co-simulation**)However, exploring software
16-28, Sept. 1993. 2] J. Rowson, **Hardware/Software co-simulation**,in 31st ACM/IEEE Design
www.ert.rwth-aachen.de/Projekte/Tools/COMPILED_SIMULATION/../PAPERS/cad_Zivojnovic95vlsi.ps.gz

An Engineering Environment for Hardware/Software Co-Simulation - Becker, Singh, Tell (1992)   (Correct)   (1 citation)
An Engineering Environment for **Hardware/Software Co-Simulation** David Becker, Raj K. Singh, Stephen
al.An Engineering environment for **Hardware-Software Co-Simulation"**In Proceedings of the 29th
129-134 An Engineering Environment for **Hardware/Software Co-Simulation** David Becker, Raj K. Singh, Stephen
ftp.cs.unc.edu/pub/projects/codesign/dac_cosim92.ps.Z

Domain-Specific Processors: Systems, Architectures.. - On Modeling Intra-Task   (Correct)
statically. In addition, a traditional **hardware/software co-simulation** stage is required in order to
carol.wins.uva.nl/~andy/artemis/samosiibook.pdf

Rapid Evaluation of Instantiations of Embedded Systems - Architectures Case Study   (Correct)
Sesame does not perform traditional **hardware/software co-simulation** [5] in which the software and
Design, November 2001. 5] J. Rowson. **Hardware/software co-simulation**. In Proc. of the Design Automation
carol.wins.uva.nl/~andy/artemis/progress01.pdf

Modeling of Intra-task Parallelism in Sesame - Andy Pimentel Frank   (Correct)
statically. In addition, a traditional **hardware/software co-simulation** stage is required in order to
carol.wins.uva.nl/~andy/artemis/samos02.pdf

IEEE October 18 - 21, 2000 Kansas City, MO - Laboratories Teaching Concepts   (Correct)
Hardware-software co-development **Hardware-software co-simulation** Partitioning tasks between
software development toolchain. **Hardware-software co-simulation** with the 8051simulation model,
fie.engrng.pitt.edu/fie2000/papers/1082.pdf

Time Accurate Simulation: Making a PC Behave Like a 8-Bit.. - Engblom, Nilsson (2002)   (Correct)
the host, not inside a simulator)**Hardware-software co-simulation**, where CPU simulators interact with
www.docs.uu.se/~jakob/publications/tr-2002-024.pdf

First 20 documents Next 20

Try your query at: Amazon   Barnes & Noble   Google (RI)   Google (Web)   CSB   DBLP

PORTAL
THE ACM DIGITAL LIBRARY

Search Results

Search Results for: **[(Hardware/Software Co-Simulation)<AND>(meta_published_date <= 02-01-2000)]**
Found **11** of **105,850 searched.**   ⟶ Rerun within the Portal

Search within Results

[   ] GO   > Advanced Search   > Search Help/Tips

Sort by: Title   Publication   Publication Date   Score   ❤ Binder

---

Results 1 - 11 of 11   short listing

1 Hardware/software co-simulation in a VHDL-based test bench approach   82%
Matthias Bauer , Wolfgang Ecker
Proceedings of the 34th annual conference on Design automation conference June 1997

2 Hardware/software co-simulation   80%
Kurt Keutzer
Proceedings of the 31st annual conference on Design automation conference June 1994

3 A compilation-based software estimation scheme for hardware/software co-simulation   77%
Marcello Lajolo , Mihai Lazarescu , Alberto Sangiovanni-Vincentelli
Proceedings of the seventh international workshop on Hardware/software codesign March 1999

4 A case study on modeling shared memory access effects during performance analysis of HW/SW systems   77%
Marcello Lajolo , Anand Raghunathan , Sujit Dey , Luciano Lavagno , Alberto Sangiovanni-Vincentelli
Proceedings of the sixth international workshop on Hardware/software codesign March 1998

5 HW/SW coverification performance estimation and benchmark for a 24 embedded RISC core design   77%
Thomas W. Albrecht , Johann Notbauer , Stefan Rohringer
Proceedings of the 35th annual conference on Design automation conference May 1998
This paper describes the benchmarking of a HW/SW-coverification design strategy. The benchmark results were the base for making a principal verification decision for an already ongoing project at Siemens AG, Public Communication Network Group. The intention for this benchmark was to verify whether commercial available coverification tools can handle the design complexity of an embedded system containing 24 embedded RISC cores and provides the necessary performance in terms of simulation spe ...

6 A reconfigurable logic machine for fast event-driven simulation   77%
Jerry Bauer , Michael Bershteyn , Ian Kaplan , Paul Vyedin
Proceedings of the 35th annual conference on Design automation conference May 1998
As the density of VLSI circuits increases, software techniques cannot effectively simulate designs through the millions of simulation cycles needed for verification. Emulation can supply the necessary capacity and performance, but emulation is limited to designs that are structural or can be synthesized. This paper discusses a new system architecture that dramatically accelerates event-driven behavioral simulation and describes how it is merged with emulation.

7 Hardware/software co-verification in ATM   77%
Giovanni Mancini
Proceedings of the seventh international symposium on High-level synthesis May 1984

8 The design of mixed hardware/software systems   77%
Jay K. Adams , Donald E. Thomas
Proceedings of the 33rd annual conference on Design automation conference June 1996

9 Symphony: a simulation backplane for parallel mixed-mode co-simulation of VLSI systems   77%
Antonio R. W. Todesco , Teresa H.-Y. Meng
Proceedings of the 33rd annual conference on Design automation conference June 1996

10 A cross-debugging method for hardware/software co-design environments   77%
Yehuda Kra
Proceedings of the 30th international on Design automation conference July 1993

11 An engineering environment for hardware/software co-simulation   77%
D. Becker , R. K. Singh , S. G. Tell
Proceedings of the 29th ACM/IEEE conference on Design automation conference July 1992

Results 1 - 11 of 11   short listing